

REMARKS


Entry of the amendments to the specification, claims and abstract before examination of the application is respectfully requested. These claims patentably define over the art of record.

If there are any questions regarding this Preliminary Amendment or the application in general, a telephone call to the undersigned would be appreciated since this should expedite the prosecution of the application for all concerned.

If necessary to effect a timely response, this paper should be considered as a petition for an Extension of Time sufficient to effect a timely response, and please charge any deficiency in fees or credit any overpayments to Deposit Account No. 05-1323 (Docket # 095309.56500US).

Respectfully submitted,

July 5, 2005
DUE DATE: July 2, 2005 (Saturday)



Donald D. Evenson
Registration No. 26,160

CROWELL & MORING LLP
Intellectual Property Group
P.O. Box 14300
Washington, DC 20044-4300
Telephone No.: (202) 624-2500
Facsimile No.: (202) 628-8844
DDE:arr

10/541311

Attorney Docket No. 095309.56500US
PCT/EP2003/014313
Substitute Specification—Marked Up Version
JC20 Rec'd PCT/PTO 05 JUL 2005

**EXHAUST GAS AFTERTREATMENT INSTALLATION AND
METHOD**

BACKGROUND AND SUMMARY OF THE INVENTION

[0001] The invention relates to an exhaust gas aftertreatment installation ~~in accordance with the preamble of claim 1 and for the~~ aftertreatment of an exhaust gas generated by a combustion device, in particular a motor vehicle internal combustion engine, having a nitrogen oxide storage catalytic converter and an SCR catalytic converter with the ability to store ammonia, which is arranged downstream of the nitrogen oxide storage catalytic converter or integrated with the latter in a common catalytic converter unit. The invention also relates to an exhaust gas aftertreatment method which can be carried out using an installation of this type. Installations and methods of this type are used in particular for the aftertreatment or purification of exhaust gases from internal combustion engines operated predominantly in lean-burn mode in motor vehicles.

[0002] The use of nitrogen oxide storage catalytic converters, also known as NO_x storage catalytic converters or NO_x adsorber catalytic converters, or NSC for short, is generally known for lowering the levels of nitrogen oxides downstream of internal combustion engines operated

- 2 -

in lean-burn mode. Lean operating phases of the internal combustion engine correspond to adsorption phases of the nitrogen oxide storage catalytic converter, in which the nitrogen oxide storage catalytic converter oxidizes nitrogen monoxide (NO) to form nitrogen dioxide (NO₂), which it temporarily stores in the form of nitrates. During brief, periodic regeneration or desorption phases, the stored nitrates are removed from the nitrogen oxide storage catalytic converter by the nitrates being converted into nitrogen dioxide and then nitrogen monoxide. The latter is then reduced to form nitrogen by suitable reducing agents.

[0003] One known technique used to provide the required reducing agents consists in switching the combustion device, which is operated predominantly in lean-burn mode and the exhaust-gas from which is being aftertreated, to rich-burn mode for a brief period of time, with the result that hydrogen (H₂), carbon monoxide (CO) and unburnt hydrocarbons (HC) are present in the exhaust gas as reducing agents. Various specific measures for controlling the air/fuel ratio, also known as the air ratio λ for short, have already been proposed for this purpose, cf. for example the laid-open specifications EP 0 560 991 A1 and DE 196 26 835 A1. The nitrogen oxide reduction may also take place in a downstream catalytic converter known as a deNO_x catalytic

- 3 -

converter; it is also possible for hydrocarbons to be metered in downstream of the engine in order to provide the reducing agents, cf. for example the laid-open specifications EP 0 540 280 A1 and EP 0 573 672 A1.

[0004] A number of problem points need to be borne in mind during this alternating adsorption/desorption operation. For example, considerable quantities of the polluting gas ammonia (NH_3) may form through reaction of hydrogen with nitrogen monoxide and/or nitrogen dioxide may form in the regeneration phase, depending on the catalytic converter temperature, the exhaust gas composition and the material composition of the nitrogen oxide storage catalytic converter. When switching from a lean exhaust gas atmosphere to a rich exhaust gas atmosphere, there is the risk of an undesirable breakthrough of nitrogen oxides on account of sudden decomposition of nitrates if suitable quantities of reducing agent are not provided quickly enough. When switching from a rich exhaust gas atmosphere to a lean exhaust gas atmosphere, the nitrogen oxide storage catalytic converter may be heated as a result of exothermic combustion reactions, with the result that nitrates which have already formed can be decomposed again and can predominantly no longer be stored, which can cause undesirable nitrogen oxide slippage. With this NO_x storage catalytic converter

- 4 -

technology, efficient lowering of the levels of nitrogen oxides is restricted to a relatively narrow temperature range, approximately between 200°C and 400°C, since at lower temperatures it is difficult to oxidize NO to form NO₂, and at higher temperatures the nitrates formed can no longer be stably stored in significant quantities, and the thermodynamic equilibrium between NO and NO₂ increasingly shifts toward nitrogen monoxide.

[0005] A further problem when using sulfur-containing fuels is what is known as sulfur poisoning of the NO_x storage catalytic converter as a result of the accumulation of sulfates, which are more stable than the nitrates and do not decompose during the NO_x regeneration phases. Therefore, special desulfating phases at elevated exhaust-gas temperature and with a rich exhaust gas composition are carried out from time to time in order to remove sulfates, cf. for example laid-open specification DE 198 27 195 A1. During desulfating, the polluting gas hydrogen sulfide (H₂S) may form; emission of this gas should be avoided. For this purpose, for example in patent DE 100 25 044 C1, it is proposed that secondary air be fed into the exhaust train during the desulfating phases, in order to oxidize the hydrogen sulfide in a downstream oxidation catalytic converter.

[0006] Another known exhaust gas aftertreatment method is the

- 5 -

process known as selective catalytic reduction, or SCR for short. In this process, a selectively acting reducing agent, typically ammonia, is added to the exhaust gas in order to reduce nitrogen oxides. The ammonia is temporarily stored in a suitable deNO_x catalytic converter, also known as an SCR catalytic converter for short, and is used by the latter to catalytically reduce nitrogen oxides (NO_x) contained in the exhaust gas to form nitrogen and water. The effectiveness of SCR catalytic converters is highly dependent on the NO/NO₂ ratio at low temperatures, with a maximum efficiency at an NO₂ level of approx. 50% for temperatures below 200°C and a greatly reduced efficiency if the NO₂ level is lower. At higher temperatures above approx. 400°C, the nitrogen oxide reduction is limited by oxidation of ammonia, and moreover the ammonia storage capacity of the SCR catalytic converter decreases as the temperature rises. The overall result for SCR systems of this type is that the temperature window which is suitable for efficiently lowering the levels of nitrogen oxides is from approximately 250°C to approximately 550°C. SCR catalytic converters are subject to thermal aging and should not be exposed to temperatures of over approximately 700°C to 750°C. At low temperatures, SCR catalytic converters may also temporarily store unburnt hydrocarbons, and even when the exhaust gas composition is rich, given a suitable design, they

- 6 -

may oxidize hydrocarbons, in particular if they contain vanadium oxide (V_2O_5) as a catalytic material.

[0007] To provide the ammonia in the exhaust gas, it is known to introduce urea, from which ammonia is formed through hydrolysis or thermolysis. One problem in this context, in particular for vehicle applications, is that a corresponding supply of urea has to be carried around. Therefore, as an alternative, internal generation of ammonia has already been proposed. For this purpose, it is proposed in laid-open specifications WO 97/17532 A1 and DE 199 49 046 A1 that an ammonia-generating catalytic converter and, downstream of the latter, an ammonia storage and nitrogen oxide reduction catalytic converter be provided, preferably with the addition of an oxygen storage catalytic converter between the two catalytic converters mentioned above or downstream of the ammonia storage catalytic converter and the nitrogen oxide reduction catalytic converter.

[0008] Laid-open specification EP 0 878 609 A1 has described an exhaust gas aftertreatment installation of the generic type, in which an NO_x storage catalytic converter and, downstream of the latter, an SCR catalytic converter are arranged in the exhaust train. As an alternative or in addition to a three-way catalytic converter, the NO_x storage catalytic converter can be designed to form ammonia when the engine is

- 7 -

briefly operated under rich-burn conditions, which is realized by an afterinjection of fuel into at least some of the engine combustion chambers. With this type of internal generation of ammonia, there is a risk of the quantity of ammonia which is generated exceeding the ammonia storage capacity of the SCR catalytic converter, resulting in undesirable ammonia slippage.

[0009] The exhaust gas aftertreatment measures described above do not lower the levels of particles, in particular of carbon particulates. It is known to use particulate filters to do this. Carbon particulates which have collected in the particulate filter can be burnt off at elevated temperature in the presence of oxygen. A standard measure for heating the particulate filter consists in introducing fuel into the exhaust gas, for example by an afterinjection, and burning this fuel in an oxidation catalytic converter connected upstream of the particulate filter. What are known as CRT systems with continuous particulate filter regeneration are also known, cf. for example US patent 4,902,487. In these systems, nitrogen dioxide is formed from NO at the oxidation catalytic converter and oxidizes the carbon particulates which have collected in the particulate filter.

[00010] To lower the levels of particulate and nitrogen oxides, laid-open specification DE 199 21 974 A1 describes an exhaust gas

- 8 -

aftertreatment installation having an oxidation catalytic converter, a downstream NO_x storage catalytic converter and a particulate filter downstream of the NO_x storage catalytic converter or between the oxidation catalytic converter and the NO_x storage catalytic converter. In the case of the former arrangement, the oxidation catalytic converter promotes the function of the NO_x storage catalytic converter through the formation of NO₂, but it is not possible to achieve a CRT effect for the particulate filter, since the nitrogen oxides are already being reduced to nitrogen upstream of the particulate filter. If the oxidation catalytic converter is used to heat the particulate filter by combustion of afterinjected fuel, this arrangement results in a high thermal loading of the NO_x storage catalytic converter and a relatively high fuel consumption. In the other arrangement described, the exhaust gas upstream of the NO_x storage catalytic converter predominantly contains NO and only a small amount of NO₂, since the latter is converted into NO by the CRT effect, with the result that the storage characteristics of the NO_x storage catalytic converter deteriorate. If the oxidation catalytic converter in this arrangement is used for desulfating-heating of the NO_x storage catalytic converter through combustion of afterinjected fuel, the high heat capacity and the heat transfer in the intervening exhaust train section means that a relatively high

- 9 -

temperature has to be reached at the oxidation catalytic converter, which can lead to thermal aging effects in the latter.

[00011] The invention is based on the technical problem of providing an exhaust gas aftertreatment installation of the type described in the introduction and an associated exhaust gas aftertreatment method with which as many of the following demands as possible can be satisfied to a high degree with relatively little outlay: effective reduction of nitrogen oxides in a wide temperature range, no need for an additional reducing agent operating medium, avoidance of ammonia and hydrogen sulfide emissions, minimal particulate emissions, particulate oxidation through NO₂ reaction, minimal CO and HC emissions, relatively low thermal loading of all the components used to purify the exhaust gas, minimal increased fuel consumption and a low demand for installation space.

[00012] The invention solves this problem by providing an exhaust gas aftertreatment installation for the aftertreatment ~~having the features of claim 1 and an exhaust gas aftertreatment method having the features of claim 11 or 12~~ of an exhaust gas generated by a combustion device, in particular a motor vehicle internal combustion engine, having a nitrogen oxide storage catalytic converter and an SCR catalytic converter with the ability to store ammonia, which is arranged downstream of the nitrogen oxide storage catalytic converter or

- 10 -

integrated with the latter in a common catalytic converter unit.

[00013] The invention also solves this problem by providing a method for the aftertreatment of an exhaust gas generated by a combustion device, in particular a motor vehicle internal combustion engine, in which nitrogen oxides contained in the exhaust gas are temporarily stored in a nitrogen oxide storage catalytic converter during adsorption operating phases of the latter and are released again from the nitrogen oxide storage catalytic converter during regeneration operating phases of the latter, with ammonia being generated, and ammonia which is generated is temporarily stored in a downstream SCR catalytic converter and is used for nitrogen oxide reduction, characterized in that the recorded nitrogen oxide content of the exhaust gas downstream of the SCR catalytic converter and/or downstream of the nitrogen oxide storage catalytic converter and/or the ammonia loading of the SCR catalytic converter is used as a criterion for the instant at which a regeneration operating phase is triggered for the nitrogen oxide storage catalytic converter. A second method of the invention provides that can further wherein nitrogen oxides contained in the exhaust gas are temporarily stored in a nitrogen oxide storage catalytic converter during adsorption operating phases of the latter and are released again from the nitrogen oxide storage catalytic converter during regeneration

- 11 -

operating phases of the latter, with ammonia being generated, and ammonia which is generated is temporarily stored in a downstream SCR catalytic converter and is used for nitrogen oxide reduction, characterized in that a desired ammonia generation quantity which is to be generated during a current regeneration operating phase of the nitrogen oxide storage catalytic converter is determined, and the subsequent regeneration operating phase is carried out as a function of the desired ammonia generation quantity determined.

[00014] In addition to a nitrogen oxide storage catalytic converter and an SCR catalytic converter connected downstream of it, the exhaust gas aftertreatment installation ~~described in claim 1~~ additionally includes a particulate filter and/or an NO₂-producing catalytic converter arranged upstream of the SCR catalytic converter.

[00015] The nitrogen oxide storage catalytic converter allows the levels of nitrogen oxides to be effectively lowered, in particular even in the case of lean-burn internal combustion engines. By virtue of its NH₃ storage capacity, the downstream SCR catalytic converter prevents undesired emission of ammonia generated by the NO_x storage catalytic converter. At the same time, the SCR catalytic converter is able to use stored ammonia to reduce any nitrogen oxide which may still be present in the exhaust gas downstream of the NO_x storage catalytic converter,

- 12 -

with the ammonia being oxidized at the same time. This effect can be exploited to deliberately form ammonia at the nitrogen oxide storage catalytic converter, in order for this ammonia to be used as reducing agent in the SCR catalytic converter. As a result, the effective lowering of the levels of nitrogen oxides can be maintained even during periods in which the temperature of the NO_x storage catalytic converter is temporarily outside its range in which it has a conversion activity, for example as a result of the exothermicity following a transition from a lean exhaust gas composition to a rich exhaust gas composition.

[00016] If nitrogen oxides are still present in the exhaust gas downstream of the NO_x storage catalytic converter, these nitrogen oxides are generally in the form of NO; the NO₂ content is much lower, amounting, for example, to at most 20%. However, at low temperatures below 300°C, the efficiency of the SCR catalytic converter is highest approximately at an NO₂ level of 50%, and significantly reduced where the NO₂ level is lower. To increase the efficiency of the SCR catalytic converter, the NO₂-producing catalytic converter may be connected upstream of it. This catalytic converter may have a relatively small volume and may have a coating which, inter alia, contains a precious metal (e.g. platinum) and is able to increase the NO₂ level in the NO_x emission to at least approximately 50% at least in a temperature range

- 13 -

from approximately 200°C to 350°C. One particular feature of the coating of the NO₂-producing catalytic converter is its property of deliberately not oxidizing ammonia which is generated in the NO_x storage catalytic converter when operating at $\lambda < 1$, but rather allowing this ammonia to pass through in unchanged form. This can be achieved, for example, by the coating not containing an oxygen-storing component.

[00017] In a corresponding control unit, which can also be used, for example, to control the combustion device, such as an internal combustion engine, it is preferable to implement functions which decide on the need for and feasibility of targeted generation of NH₃ and preset the operating parameters, in particular the duration and extent of enrichment during NSC regeneration, in a suitable way. The formation of NH₃ can typically be boosted by a lower air ratio and a longer regeneration time, provided that the temperature of the NO_x storage catalytic converter is in the range in which NH₃ formation is possible. Furthermore, operation of the combustion device during NSC regeneration can be set in a manner known per se such that high untreated NO_x emissions from the combustion device result, and as a result the formation of NH₃ at the NO_x storage catalytic converter is boosted further.

- 14 -

[00018] It has been found that the SCR catalytic converter can also be used to avoid H₂S emission, produced, for example, during desulfating. Tests have shown that an SCR catalytic converter, on account of its specific properties, can oxidize hydrogen sulfide formed during the desulfating to form SO₂ even at a rich exhaust gas composition ($\lambda < 1$). This makes it possible to avoid unpleasant odor pollution.

[00019] As a further particular feature, SCR catalytic converters, provided that they contain vanadium oxide, can even oxidize unburnt hydrocarbons (HC) during rich conditions ($\lambda < 1$). This makes it possible to reduce the extent to which reducing agent breaks through during NSC regeneration. In particular, by way of example, it is possible to lower the emission levels of possibly carcinogenic hydrocarbons, such as benzene, toluene, ethylbenzene and xylene, which can form under rich conditions at the NO_x storage catalytic converter. On account of its ability to store hydrocarbons even at low temperatures, the SCR catalytic converter can additionally make a contribution to lowering the levels of HC emissions following a cold start. The HC which have been stored at low temperatures are released again at higher temperatures and can be oxidized at the SCR catalytic converter or a downstream oxidation catalytic converter.

[00020] A particulate filter can be used for lowering the levels of

- 15 -

particulates downstream of the engine. This particulate filter highly efficiently retains the particulates emitted. As is customary, the particulates which have collected can be burnt off at regular intervals by increasing the temperature to over 600°C. If the exhaust gas reaching the particulate filter contains NO₂, particulate oxidation also takes place even in the temperature range between approximately 250°C and 400°C as a result of reaction with NO₂ (CRT effect). The particulate filter may generally be catalytically coated, in which case the coating may contain components such as a precious metal (e.g. platinum) and a washcoat.

[00021] The maximum thermal loading of the individual components can be adapted to the specific requirements by using a suitable arrangement of the components. Moreover, by using a suitable arrangement it is possible to ensure that the temperatures of the individual components are within a range which is expedient for the corresponding function when the vehicle is driving. The rich-burn operation which is required for the regeneration of the NO_x storage catalytic converter can be realized by engine-internal measures or additional introduction of reducing agent (e.g. fuel or hydrogen) downstream of the engine.

[00022] The heating of the NO_x storage catalytic converter for

- 16 -

desulfating purposes and of the particulate filter for thermal regeneration purposes can be effected by engine-internal measures, including afterinjection of fuel. In addition to the deliberately increased exhaust gas temperature, incompletely burnt hydrocarbons which remain in the exhaust gas lead to additional exothermicity at a catalytic converter optionally arranged close to the engine, with the result that the exhaust gas temperature is increased further. In addition or as an alternative, it is also possible for reducing agent (e.g. fuel or hydrogen) to be supplied in the exhaust train directly upstream of the component(s) to be heated or upstream of an oxidation catalytic converter connected upstream of these components. This has the advantage that the heat losses involved in heating further upstream components and heat losses resulting from cooling in the exhaust pipe are reduced. This restricts the outlay on energy and therefore the increased fuel consumption for the heating to a minimum. A further advantage is that in this way further upstream components are not subjected to high exhaust gas temperatures, and consequently the thermal aging of these components can be restricted to a minimum. Moreover, this prevents further upstream components, e.g. an upstream NO_x storage catalytic converter, from leaving the temperature window required for high efficiency as a result of the heating.

- 17 -

[00023] In the case of a catalytically coated particulate filter, a further advantage is that the conversion of fuel, on account of the high heat capacity of the particulate filter, continues to be possible even, for example, after prolonged overrun phases of the internal combustion engine with a low exhaust gas temperature. By contrast, when using a conventional catalytic converter, there is a risk that, on account of the low heat capacity, the temperature will drop below the light-off temperature under comparable conditions, meaning that catalytic conversion of the hydrocarbons will no longer be possible. In general terms, other heating methods are possible as an alternative to supplying reducing agent (e.g. hydrogen or fuel) upstream of a catalytic converter. These other methods are not expressly mentioned below but can be used instead of supplying reducing agent downstream of the engine. In this context, by way of example, mention may be made of an electrically heated catalytic converter, electrical heating of the particulate filter or the use of a burner as standard conventional measures.

[00024] The supply of reducing agent downstream of the engine and upstream of the NO_x storage catalytic converter can also be utilized to set rich conditions for NSC regeneration when the engine is operating with lean exhaust gas. This is preferably implemented when the engine

- 18 -

is operating between $\lambda = 1.0$ and $\lambda = 1.2$, since otherwise the quantity of reducing agent to be supplied is too great. This results in the advantage that high untreated NO_x emission usually occurs in the range between $\lambda = 1.0$ and $\lambda = 1.2$, whereas the level of untreated NO_x emissions is considerably lower at air ratios of $\lambda < 1$. Consequently, this method can be used to achieve a high level of NO_x emission and therefore extensive formation of NH_3 during NSC regeneration.

[00025] To avoid high emissions of CO and HC during NSC regeneration operations with $\lambda < 1$, if necessary secondary air can be blown in ahead of a downstream oxidation catalytic converter. The secondary air can, for example, be provided by an electrically driven secondary air pump or a compressor or, in the case of supercharged engines can be removed downstream of the compressor.

[00026] It is possible to considerably reduce the overall space taken up by optionally combining or integrating two of the abovementioned functionalities in one component, for example, by applying a catalytic coating to a particulate filter.

[00027] In further configurations, the exhaust gas aftertreatment installation contains one or more NO_x sensors downstream of the NO_x storage catalytic converter and/or the SCR catalytic converter, and/or means for recording the temperature of one or more of the exhaust gas

- 19 -

purification components and/or means for recording the NH_3 loading of the SCR catalytic converter.

[00028] Various possible implementations are possible for the order in which the NO_x storage catalytic converter, SCR catalytic converter, particulate filter and NO_2 -producing catalytic converter are arranged in the exhaust train, each of these implementations having specific properties and advantages; the options include multi-flow arrangements.

[00029] The basic method described in ~~claim 11~~ above allows relatively accurate, model-based control of the time at which a regeneration of the nitrogen oxide storage catalytic converter is initiated.

[00030] The second method described in ~~claim 12~~ above allows targeted control of the generation of ammonia during a respective regeneration phase of the nitrogen oxide storage catalytic converter taking account of the current conditions, in particular with regard to the temperatures of the ammonia-generating NO_x storage catalytic converter and of the SCR catalytic converter and/or the ammonia loading of the SCR catalytic converter; a variable quantity of ammonia which is to be generated during the current regeneration phase of the NO_x storage catalytic converter can be predetermined as a function of

- 20 -

the operating state which has been ascertained.

[00031] In one configuration of this method, the results of the determination as to whether the exhaust gas air ratio downstream of the NO_x storage catalytic converter has dropped below a threshold value, which is dependent on the quantity of ammonia which it is desired to form, can be used as a criterion for terminating a regeneration phase of the NO_x storage catalytic converter.

[00032] In a further configuration of the method according to the invention, an external supply of reducing agent, e.g. downstream of the engine, into the exhaust train can be provided for during the NSC regeneration, in order for the combustion device also to be operated under lean-burn conditions during this period, resulting in high untreated NO_x emissions from the combustion device.

[00033] In a further configuration of the method, it is possible to provide for secondary air to be fed into the exhaust train at a suitable location during the rich-burn operating phases, in order to oxidize any NH₃, H₂S, CO and HC which may be present during these operating phases and thereby to prevent corresponding emissions of pollutants.

[00034] Advantageous embodiments of the invention are illustrated in the drawings and described below. ~~In the drawings:~~

BRIEF DESCRIPTION OF THE DRAWINGS

[00035] Figure 1 shows a schematic block diagram illustration of an internal combustion engine of a motor vehicle with connected single-flow exhaust gas aftertreatment installation, which includes, connected in series, a first oxidation catalytic converter, a particulate filter, an NO_x storage catalytic converter, an NO₂-producing catalytic converter, an SCR catalytic converter and a second oxidation catalytic converter,

[00036] Figure 2 shows a schematic block diagram illustration in accordance with Figure 1, but with a modified exhaust gas aftertreatment installation which includes, connected in series, an NO_x storage catalytic converter, an NO₂-producing catalytic converter, a particulate filter, an SCR catalytic converter and an oxidation catalytic converter,

[00037] Figure 3 shows a schematic block diagram illustration in accordance with Figure 1, with a modified exhaust gas aftertreatment installation, which includes, connected in series, an NO_x storage catalytic converter, an NO₂-producing catalytic converter, an SCR catalytic converter, an oxidation catalytic converter and a particulate filter,

[00038] Figure 4 shows a schematic block diagram illustration in accordance with Figure 1, but with a modified exhaust gas

- 22 -

aftertreatment installation, which includes a first oxidation catalytic converter, an integrated nitrogen oxide storage and SCR catalytic converter, a second oxidation catalytic converter and a particulate filter, and

[00039] Figure 5 shows a schematic block diagram illustration in accordance with Figure 1, but for a modified internal combustion engine with a two-flow exhaust train and associated two-flow exhaust gas aftertreatment installation.

DETAILED DESCRIPTION OF THE DRAWINGS

[00040] The exhaust gas aftertreatment installation illustrated in Figure 1 includes, downstream of an internal combustion engine 1, as seen in the direction of flow of the exhaust gas, in an exhaust train 3, the following successive components: an oxidation catalytic converter 4, a particulate filter 5, an NO_x storage catalytic converter 6, an NO₂-producing catalytic converter 13, an SCR catalytic converter 7 and a further oxidation catalytic converter 4 as exhaust gas purification components. A control unit 2 is used to control the internal combustion engine 1, which may, for example, be a standard diesel or spark-ignition engine, and the exhaust gas aftertreatment installation. Furthermore, there are temperature sensors 8, NO_x sensors 9, lambda sensors 10,

- 23 -

devices 11 for supplying reducing agent downstream of the engine, a device 12 for supplying secondary air and pressure sensors 14 provided at suitable locations in the exhaust train 3, as shown.

[00041] The internal combustion engine 1 delivers exhaust gas containing, inter alia, NO_x particulates, CO and HC. During standard lean-burn operation of the internal combustion engine 1, CO and HC are oxidized at the oxidation catalytic converter 4 to form CO₂ and H₂O. Moreover, some of the NO contained in the exhaust gas is oxidized to form NO₂. The particulates which are present in the exhaust gas are retained in the particulate filter 5. Some of the carbon particulates which have collected in the particulate filter 5 are oxidized by reaction with NO₂, with NO₂ being reduced to NO. The nitrogen oxides contained in the exhaust gas are stored in the NO_x storage catalytic converter 6. If nitrogen oxides are still present in the exhaust gas downstream of the NO_x storage catalytic converter 6, these nitrogen oxides are generally in the form of NO; the NO₂ level is significantly lower, amounting, for example, to at most 20%. However, the efficiency of the SCR catalytic converter 7 at low temperatures below 300°C is highest at an NO₂ level of approximately 50% and is significantly reduced if the level of NO₂ is lower. Therefore, the NO₂-producing catalytic converter 13 is connected upstream of the SCR catalytic

- 24 -

converter 7. This catalytic converter 13 has a coating which contains, inter alia, precious metal (e.g. platinum) and is able to increase the level of NO₂ in the total emission of NO_x to at least approximately 50%, at least in a temperature range from approximately 200°C to 350°C. One particular feature of the coating of the NO₂-producing catalytic converter is its ability of deliberately not oxidizing ammonia generated in the NO_x storage catalytic converter during operation at $\lambda < 1$ but rather allowing this ammonia to pass through in unchanged form. This can be achieved, for example, by the coating not containing any oxygen-storing components. The SCR catalytic converter 7 is able to reduce the nitrogen oxide with the aid of NH₃ stored therein. In this case, the efficiency at temperatures below 300°C is increased by the NO₂-producing catalytic converter 13 connected upstream.

[00042] Heating measures can be employed to ensure that sufficient temperatures are reached at all the components, in particular at the NO_x storage catalytic converter 6 and SCR catalytic converter 7, even during low-load operation, and thereby to ensure optimum lowering of the levels of NO_x. These heating measures may be engine-internal, e.g. a shift towards the late position for the main injection or an afterinjection, or may take place downstream of the engine, as a result of reducing agent being supplied upstream of the NO_x storage catalytic

- 25 -

converter, in order to generate exothermicity, provided that the NO_x storage catalytic converter 6 has reached a sufficient temperature to convert the reducing agent. Further measures for increasing the exhaust gas temperature may include, increasing the idling speed, lengthening the afterglow time, connecting up additional electrical consumers or increasing the EGR rate. The abovementioned heating measures can be controlled, for example, by the control unit 2 as a function of the incoming temperature sensor signals or by means of a model. The exhaust pipe 3 may be thermally insulated in order to minimize heat losses from the exhaust gas. By way of example, it is possible to use an air gap insulation.

[00043] NSC regenerations are required at regular intervals. The times for regeneration operations are determined with the aid of the NO_x sensor 9 downstream of the SCR catalytic converter. The signal from the NO_x sensor 9 is recorded and assessed in the control unit 2. If the breakthrough of NO_x is unacceptably high, for example if it exceeds a certain proportion of the untreated NO_x emissions (e.g. NO_x content downstream of NO_x storage catalytic converter > 10% of the untreated NO_x emissions), the control unit 2 requests an NSC regeneration. If criteria which are taken into account in the control unit 2 and are a precondition on the engine side for an NSC regeneration to be realized

- 26 -

are satisfied, for example, operation in a specific part of the operating range of the engine 1 in which NSC regeneration can be effected, the NSC regeneration is initiated.

[00044] Models for the untreated NO_x emission, the NO_x storage capacity of the NO_x storage catalytic converter 6, the NH₃ formation at the NO_x storage catalytic converter and the NH₃ storage in the SCR catalytic converter 7 are stored in the control unit 2. These models can be used to assess the NO_x sensor signal downstream of the SCR catalytic converter and can also be used for diagnostic purposes. The models can be adapted to the current state of aging of the catalytic converters on the basis of the sensor signals. Alternatively, the aging state can be diagnosed by comparing the sensor signals from the NO_x sensors 9 and/or the lambda sensors 10 with the modeled behavior of the catalytic converters, without, however, adapting the model.

[00045] As an alternative to considering the NO_x signal downstream of the SCR catalytic converter, or as an additional option, it is possible to request an NSC regeneration when the modeled SCR loading with NH₃ drops below a relative value, e.g. 5% of the possible NH₃ loading, or an absolute value, e.g. 0.1 g of NH₃.

[00046] As an alternative to considering the NO_x signal downstream of the SCR catalytic converter, it is also possible to consider the signal

- 27 -

from the NO_x sensor 9 downstream of the NO_x storage catalytic converter. This can be assessed in a similar way to the procedure described above and can be used as a criterion to demand an NSC regeneration.

[00047] Alternatively the signal from the NO_x sensor 9 downstream of the NO_x storage catalytic converter can be used as an input variable for the NSC model in the control unit 2. The nitrate loading of the NO₂ storage catalytic converter 6 can be calculated with the aid of the model, thereby allowing the NH₃ formation to be estimated taking the aging into account. Since the NH₃ loading of the SCR catalytic converter 7 is likewise calculated by means of a model, it is possible to request an NSC regeneration if the modeled SCR loading with NH₃ drops below a relative value, e.g. 5% of the possible NH₃ loading, or an absolute value, e.g. 0.1 g of NH₃.

[00048] In principle, it is also possible to use both NO_x sensors 9, in which one sensor, as described above, delivers a criterion for requesting an NSC regeneration and the second NO_x sensor is used to diagnose and adapt the catalytic converter model in the control unit 2. In addition, an NH₃ sensor (not shown in Figure 1) can be provided downstream of the NO_x storage catalytic converter and also downstream of the SCR catalytic converter; the signal from this NH₃ sensor can be

- 28 -

used to adapt the models of the NO_x storage catalytic converter 6 and the SCR catalytic converter 7 or to control the regeneration parameters.

[00049] The control unit 2 includes functions which decide upon the need for and feasibility of controlled generation of NH₃ during an impending NSC regeneration and predetermine the operating parameters, in particular the duration and degree of enrichment, accordingly. An important criterion in this respect is the temperatures of the NO_x storage catalytic converter 6 and of the SCR catalytic converter 7. The temperatures are determined by the temperature sensors 8 in or downstream of the respective components. Alternatively, the temperature of the SCR catalytic converter 7 can be calculated on the basis of the measured temperature downstream of the NO_x storage catalytic converter, with the aid of a model in the control unit 2, so that there is no need for the sensor 8 downstream of the SCR catalytic converter. In addition to the temperatures of the NO_x storage catalytic converter 6 and of the SCR catalytic converter 7, it is also possible, for example, for the current NH₃ loading, calculated by model means, of the SCR catalytic converter 7 to be used as a criterion.

[00050] If the temperatures of the NO_x storage catalytic converter 6 and of the SCR catalytic converter 7 are within predetermined ranges, the current NH₃ loading of the SCR catalytic converter 7 is low and any

- 29 -

further conditions are satisfied, maximum formation of NH_3 is desired. If the temperature of the NO_x storage catalytic converter 6 is outside the predetermined range, which may, for example, be between 230°C and 370°C , formation of NH_3 is not possible or is only possible to a limited extent and is therefore also not aimed for. This avoids unnecessarily increased fuel consumption and high levels of HC and CO emissions on account of the regeneration lasting too long. If the temperature of the SCR catalytic converter 7 is outside the predetermined range, which may, for example, be between 200°C and 450°C , formation of NH_3 is likewise not aimed for, or only a small amount is aimed for, since either NH_3 cannot be sufficiently stored in the SCR catalytic converter 7 and therefore would be emitted or conversion of NO_x at the SCR catalytic converter 7 is scarcely possible. The same applies to the situation in which the current NH_3 loading of the SCR catalytic converter 7 is so high that it is impossible for further NH_3 to form.

[00051] In general, in addition to the current temperatures, in particular in the case of the SCR catalytic converter 7, it is also possible to take account of temperature gradients, e.g. a rapid rise, and/or to implement a temperature prediction. The predicted temperature is then taken into account in addition to the current temperature. By way of

- 30 -

example, reduced formation of NH_3 is aimed for if a strong increase in the temperature of the SCR catalytic converter 7 is predicted, since otherwise there is a risk of subsequent NH_3 desorption in the SCR catalytic converter 7. The state of aging of the NO_x storage catalytic converter 6 is likewise taken into account when deciding on the formation of NH_3 which is aimed for, since the reduction of NO_x in the SCR catalytic converter 7 becomes increasingly important with progressive aging of the NO_x storage catalytic converter 7.

[00052] The optimum air ratio is defined in the control unit 2 as a function of the NH_3 which is aimed for. If it is aimed to form high levels of NH_3 an air ratio for maximum formation of NH_3 is preset. If this is not the case, an air ratio for the formation of small amounts or no NH_3 is preset. Intermediate values for the formation of medium amounts of NH_3 are also possible. The air ratio can also be varied continuously or in steps during the NSC regeneration as a function of the temperatures of NO_x storage catalytic converter 6 and SCR catalytic converter 7 and further parameters. By way of example, a lower air ratio can be set at the start and a higher air ratio can be set as regeneration progresses, in order to form high levels of NH_3 combined, at the same time, with low emissions of HC and CO during the NSC generation.

[00053] The duration of the NSC regenerations is likewise set as a

- 31 -

function of the desired formation of NH_3 . The gradual drop in the air ratio downstream of the NO_x storage catalytic converter 6 to values of lower than $\lambda = 1$ is used to this end as a criterion for terminating the NSC regeneration. If it is aimed to form high levels of NH_3 , the regeneration is terminated as soon as the air ratio determined by the lambda sensor 10 downstream of the NO_x storage catalytic converter drops below a threshold value λ_1 . It is optionally also possible to continue a predetermined time or number of working cycles of the engine 1 beyond this point. If the aim is for no NH_3 to be formed, the regeneration is terminated immediately as soon as the air ratio downstream of the NO_x storage catalytic converter drops below a threshold value λ_2 , where λ_2 is greater than λ_1 . As a result, breakthroughs of HC/CO are substantially avoided and a low increased fuel consumption is achieved. The threshold values can be varied as a function of the NSC aging and further parameters. Intermediate values are also possible in order to achieve the formation of a medium level of NH_3 .

[00054] As soon as the aim is to form high levels of NH_3 , operation of the engine during NSC regeneration is additionally set in such a way that the untreated NO_x emissions from the engine 1 are as high as possible. This can be effected in combination with a supply of reducing

- 32 -

agent downstream of the engine and upstream of the NO_x storage catalytic converter 6. This further boosts the formation of NH₃ at the NO_x storage catalytic converter 6. If the aim is for no NH₃ formation, by contrast, the engine operation is set in such a way that the untreated NO_x emissions from the engine are as low as possible.

[00055] The device 11 arranged upstream of the NO_x storage catalytic converter 6 for supplying reducing agent downstream of the engine is used to heat up the NO_x storage catalytic converter 6 for a desulfating operation. This measure is carried out in addition to measures taken at the engine for heating. The boost provided by the supply of reducing agent downstream of the engine makes it possible to reduce the extent of the measures taken at the engine, so that the thermal aging of the oxidation catalytic converter is reduced. Heating of the NO_x storage catalytic converter 6 exclusively by supplying reducing agent downstream of the engine is not desirable, since the large quantity of reducing agent would generate considerable exothermicity at the NO_x storage catalytic converter 6, which would lead to thermal aging. The quantity of reducing agent supplied is controlled, inter alia, as a function of the following parameters: the desired temperature of the NO_x storage catalytic converter 6, the actual temperature downstream of the particulate filter, the actual temperature downstream of the NO_x

- 33 -

storage catalytic converter and the mass flow of exhaust gas.

[00056] Furthermore, at least one of the two devices illustrated in Figure 1 for supplying reducing agent downstream of the engine can be used to maximize the untreated NO_x emissions from the engine 1 during the NSC regeneration. For this purpose, the engine 1 is operated with an air ratio $\lambda > 1$ at which a high NO_x emission level is reached, preferably between $\lambda = 1.0$ and $\lambda = 1.2$. The supply of reducing agent downstream of the engine allows the air ratio upstream of the NO_x storage catalytic converter to be lowered to $\lambda < 1$.

[00057] Thermal regenerations of the particulate filter 5 are required at regular intervals. This may be the case, for example, if a high pressure drop at the particulate filter 5 is recorded by the pressure sensors 14 upstream and downstream of the particulate filter, implying unacceptably high loading of the particulate filter 5. The device 11 for supplying reducing agent downstream of the engine which is arranged upstream of the particulate filter 5 and the oxidation catalytic converter 4 connected upstream of the particulate filter 5 can be used to heat the particulate filter 5. This measure is carried out in addition to engine-internal measures for raising the exhaust gas temperature. The boost provided by the supply of reducing agent downstream of the engine makes it possible to reduce the extent of engine-internal measures. It is

- 34 -

not desirable for the oxidation catalytic converter 4 and therefore the particulate filter 5 to be heated exclusively by supplying reducing agent downstream of the engine, since the large quantity of reducing agent would generate extensive exothermicity at the oxidation catalytic converter 4, which would lead to thermal aging. The quantity of reducing agent supplied is controlled, inter alia, as a function of the following parameters: the desired temperature of the particulate filter 5, the actual temperature upstream of the particulate filter, the actual temperature downstream of the particulate filter and the mass flow of exhaust gas.

[00058] The device 12 for supplying secondary air and the further oxidation catalytic converter 4 are connected downstream of the SCR catalytic converter 7. This oxidation catalytic converter 4 may be significantly smaller and also, for example, have a lower precious metal loading than the oxidation catalytic converter 4 upstream of the particulate filter. The device 12 for supplying secondary air is activated whenever the engine 1 is being operated with $\lambda < 1$. Undesirable emissions, such as NH_3 , H_2S and CO and HC , may form during these phases. These components can be oxidized in the oxidation catalytic converter 4 connected downstream of the device 12 for supplying secondary air, so that emission of these undesirable components is

- 35 -

avoided.

[00059] For this purpose, the quantity of secondary air supplied is set in such a way that, despite the engine operating at $\lambda < 1$, a lean exhaust gas composition ($\lambda > 1$) is achieved at the downstream oxidation catalytic converter 4. Inter alia, the signal from at least one lambda sensor 10 and the mass flow of exhaust gas are used in the control unit 2 to control the quantity of secondary air supplied. If the device 12 for supplying secondary air is able to provide sufficient quantities of secondary air only after a certain delay time, it is in each case activated a corresponding time before the changeover to operation with $\lambda < 1$.

[00060] It is advantageous in this exemplary embodiment that the SCR catalytic converter 7 is protected from high temperatures downstream of the particulate filter during the thermal regeneration of the particulate filter 5, since the length of the exhaust pipe means that the exhaust gas has been considerably cooled by the time it reaches the SCR catalytic converter 7, and moreover, the NO_x storage catalytic converter 6 acts as a heat sink. In this way, the thermal aging of the SCR catalytic converter 7 can be kept at a low level. As a further advantage, the high heat capacity of the particulate filter 5 stabilizes the temperatures of the downstream components even when the vehicle driving conditions are not in a steady state. This ensures that the NO_x

- 36 -

storage catalytic converter 6 and the SCR catalytic converter 7 are generally in a favorable temperature range even when the vehicle driving conditions are not in a steady state, and therefore the system operates highly efficiently. Moreover, the risk of undesirable desorption of stored NH_3 at the SCR catalytic converter 7 as a result of a rapid increase in temperature is minimized.

[00061] The particulate filter 5 may be catalytically coated. The catalytic coating of the particulate filter 5 may be similar to the coating of one of the oxidation catalytic converters 4. As a result, the upstream oxidation catalytic converter 4 can be made smaller or provided with a lower precious metal content, which leads to space and/or cost benefits. If appropriate, the oxidation catalytic converter 4 connected upstream of the particulate filter 5 can also be dispensed with altogether. In this case, the temperature sensor 8 upstream of the particulate filter 5 is likewise removed. Therefore, it is no longer the temperature upstream of the particulate filter, but rather the temperature downstream of the particulate filter which is used as control variable when heating the particulate filter 5 for thermal regeneration. However, the catalytic coating of the particulate filter 5 may also be similar to the coating of the NO_x storage catalytic converter 6. This allows the downstream NO_x storage catalytic converter 6 to be of smaller design, which leads to

- 37 -

space and/or cost benefits. If appropriate, it is also possible for the separate NO_x storage catalytic converter 6 to be dispensed with altogether, i.e. for it to be integrated in the particulate filter 5.

[00062] It should be noted that at least some of the temperature sensors 8 can also be dispensed with. It is likewise also possible to eliminate some or all of the NO_x sensors 9. In this case, the components contained in the exhaust gas aftertreatment system are modeled in the control unit 2 in such a way that the NO_x concentrations or temperatures which occur at the respective positions are available as output variables of the model. It is also possible for one or both of the devices 11 for supplying reducing agent downstream of the engine to be dispensed with. The device 12 for supplying secondary air and the downstream oxidation catalytic converter 4 can likewise be dispensed with.

[00063] The NO₂-producing catalytic converter 13 may, as illustrated in Figure 1, be designed as a separate component. Alternatively, it is also possible for it to be integrated at the outlet end of the NO_x storage catalytic converter 6 or at the inlet end of the SCR catalytic converter 7. Alternatively the NO₂-producing catalytic converter 13 can also be dispensed with.

[00064] The exemplary embodiment shown in Figure 2 differs from

- 38 -

that shown in Figure 1 in that the NO_x storage catalytic converter 6 forms the first exhaust gas purification component, which is then followed in the downstream direction by the NO₂-producing catalytic converter 13, the particulate filter 5, the SCR catalytic converter 7 and the downstream oxidation catalytic converter 4, in the order listed, while the other, upstream oxidation catalytic converter is no longer present. Functionally equivalent components are denoted by the same reference designations in Figure 2 as in Figure 1. The following explanations of the exemplary embodiment shown in Figure 2 can be restricted to the differences which result from the different order of the exhaust gas purification components; otherwise, the properties and advantages which have been explained above in connection with the exemplary embodiment shown in Figure 1 apply accordingly.

[00065] Therefore, in the example shown in Figure 2, the NO_x storage catalytic converter 6 performs the function of oxidizing CO and HC to form CO₂ and H₂O during standard lean-burn operation of the internal combustion engine 1 and to temporarily store a significant proportion of the nitrogen oxides contained in the exhaust gas.

[00066] In this case the NO₂-producing catalytic converter 13 is connected directly upstream of the particulate filter 5, in order to increase the level of NO₂ in the nitrogen oxides which are still present

- 39 -

in the exhaust gas downstream of the NO_x storage catalytic converter 6 depending on the operating state, typically from at most 20% to at least approximately 50%. This makes it possible to promote the oxidation of carbon particulates in the particulate filter 5 by reaction with NO₂ (CRT effect) and to increase the efficiency of the downstream SCR catalytic converter 7. These effects can be boosted further by admitting a maximum NO_x slippage at the NO_x storage catalytic converter 6, so that the NO_x reduction potential of the SCR catalytic converter 7 can be exploited to its maximum extent. At temperatures below 300°C, the efficiency is also increased by the NO₂-producing catalytic converter 13 connected upstream of the particulate filter 5.

[00067] In the arrangement shown in Figure 2, once again, the device 11 for supplying reducing agent downstream of the engine, which is in this case positioned directly upstream of the NO₂-producing catalytic converter 13, can be used to heat the particulate filter 5, making it possible to reduce the extent of engine-internal measures required for this purpose, thereby reducing aging effects in the NO_x storage catalytic converter 6. It is not desirable to heat the NO₂-producing catalytic converter 13 purely by the supply of reducing agent downstream of the engine, on account of thermal aging effects in this catalytic converter. The quantity of reducing agent supplied is controlled inter alia as a

- 40 -

function of the following parameters: the desired temperature of the particulate filter 5, the actual temperature upstream of the NO₂-producing catalytic converter and downstream of the NO_x storage catalytic converter, the actual temperature downstream of the particulate filter and the mass flow of exhaust gas.

[00068] An advantage of the exemplary embodiment shown in Figure 2 is that the NO_x storage catalytic converter 6, on account of being positioned close to the engine, reaches the required operating temperature soon after a cold start. This means that few measures are required to erase the exhaust gas temperature. This reduces the increased fuel consumption resulting from heating measures. Furthermore, in this exemplary embodiment, the SCR catalytic converter 7 is protected from high temperatures during the desulfating of the NO_x storage catalytic converter 6, since the length of the exhaust pipe results in considerable cooling of the exhaust gas by the time it reaches the SCR catalytic converter 7, and in addition, the particulate filter 5 and the NO₂-producing catalytic converter 13 act as heat sinks. In this way, the thermal aging of the SCR catalytic converter 7 can be kept at a low level. As a further advantage, the high heat capacity of the particulate filter 5 leads to stabilization of the temperature of the downstream SCR catalytic converter 7 even when the vehicle driving

- 41 -

operation is not in a steady state. This ensures that the SCR catalytic converter 7 is generally in a suitable temperature range, and therefore works with a high level of efficiency, even when the vehicle driving operation is not in a steady state. In addition, the risk of undesirable desorption of stored NH_3 at the SCR catalytic converter 7 as a result of a rapid increase in temperature is minimized.

[00069] The particulate filter 5 may be catalytically coated. The catalytic coating of the particulate filter 5 may be similar to the coating of the NO_2 -producing catalytic converter 13. As a result, the upstream NO_2 -producing catalytic converter 13 can be made smaller or given a lower precious metal content, which leads to space and/or cost benefits. If appropriate, it is also possible for the NO_2 -producing catalytic converter connected upstream of the particulate filter 5 to be dispensed with altogether.

[00070] However, the catalytic coating of the particulate filter 5 may also be similar to the coating of the NO_x storage catalytic converter 6. This allows the NO_x storage catalytic converter 6 arranged close to the engine to be of smaller design, which leads to space and/or cost benefits. If appropriate, it is also possible for the separate NO_x storage catalytic converter 6 to be dispensed with altogether, i.e. for its function to be integrated in the particulate filter 5. In this case, it is also possible for

- 42 -

both the NO₂-producing catalytic converter 13 and the device 11 for supplying reducing agent downstream of the engine and upstream of the NO₂-producing catalytic converter 13 to be dispensed with. However, the pressure sensor 14 illustrated upstream of the particulate filter is retained, and the NO_x sensor 9, illustrated downstream of the NO_x storage catalytic converter 6 in Figure 2, and the lambda sensor 10 are then positioned downstream of the particulate filter 5.

[00071] Furthermore, the catalytic coating may also be similar to the coating of the downstream SCR catalytic converter 7. This allows the SCR catalytic converter 7 to be of smaller design, which leads to space and/or cost benefits. If appropriate, the SCR catalytic converter as a separate component can also be dispensed with altogether. In this case, the temperature sensor 8 illustrated in Figure 2 between particulate filter and SCR catalytic converter can be dispensed with, but the pressure sensor 14 illustrated downstream of the particulate filter is retained.

[00072] Instead of being arranged upstream of the particulate filter 5, the NO₂-producing catalytic converter 13 may also be integrated at the outlet end of the NO_x storage catalytic converter 6. Alternatively, the NO₂-producing catalytic converter 13 may also be arranged upstream of the SCR catalytic converter 7. As a further possible option, it is also

- 43 -

possible for the NO₂-producing catalytic converter 13 to be integrated at the inlet end of the SCR catalytic converter 7. Alternatively, the NO₂-producing catalytic converter 13 can also be dispensed with altogether.

[00073] Although this is not illustrated in Figure 2, it is additionally possible for a further oxidation catalytic converter to be connected upstream of the NO_x storage catalytic converter 6, which can further lower the emissions of HC and CO in particular during a cold start.

[00074] As a further variant, Figure 3 shows an exhaust gas aftertreatment installation which differs from that shown in Figure 2 by virtue of the fact that the positions of particulate filter 5 and SCR catalytic converter 7 are switched, and the oxidation catalytic converter 4 is connected directly upstream of the particulate filter 5. Moreover, the other components, i.e. the various sensors 8, 9, 10, 14, the devices 11 for supplying reducing agent downstream of the engine and the secondary air feed device 12 are arranged at modified positions suitably matched to the associated exhaust gas purification components 4 to 7, 13 in the exhaust train 3, in the same way as was the case in the example shown in Figure 2 with respect to that shown in Figure 1. As in the exemplary embodiment explained above with reference to Figure 2, the following text will deal only with those measures and

- 44 -

resulting effects of the example shown in Figure 3 which differ from those of the examples shown in Figs. 1 and 2, while otherwise reference can be made, in connection with the corresponding functions and properties to the statements made above in connection with the examples illustrated in Figs. 1 and 2.

[00075] The NO₂-producing catalytic converter 13, which in the example shown in Figure 3 is connected directly upstream of the SCR catalytic converter 7, once again allows the efficiency of the SCR catalytic converter 7 to be noticeably increased, in particular in the temperature range below 300°C.

[00076] In this case, the device 11 for supplying reducing agent downstream of the engine which is connected upstream of the oxidation catalytic converter 4 before the particulate filter 5 can be used to heat the particulate filter 5. In this arrangement, the NO_x storage catalytic converter 6 and the SCR catalytic converter 7 are not thermally loaded by this measure. Heating of the particulate filter exclusively by the supply of reducing agent downstream of the engine is not desirable, in order not to cause excessive thermal aging of the oxidation catalytic converter 4. The quantity of reducing agent supplied is controlled, inter alia, as a function of the following parameters: the desired temperature of the particulate filter 5, the actual exhaust gas temperature upstream

- 45 -

of the oxidation catalytic converter 4 or downstream of SCR catalytic converter 7, the actual exhaust gas temperature downstream of the particulate filter 5 and the mass flow of exhaust gas.

[00077] An advantage of the example shown in Figure 3 is that in addition to the NO_x storage catalytic converter 6, the SCR catalytic converter 7, by virtue of its position downstream of the NO_x storage catalytic converter 6, reaches the required operating temperature relatively quickly after a cold start. A further advantage is that there is no need for an additional oxidation catalytic converter as a final component of the system in order to oxidize the undesirable exhaust gas components by blowing in secondary air. Moreover, in this exemplary embodiment the SCR catalytic converter 7 is protected from high temperatures during the thermal regeneration of the particulate filter 5, since it is positioned upstream of the particulate filter 5.

[00078] The particulate filter 5 may be catalytically coated, in which case the catalytic coating may be similar to that of the upstream oxidation catalytic converter 4, so that the latter can be made smaller or given a lower precious metal content, which leads to space and/or cost benefits. It is optionally also possible for the oxidation catalytic converter connected upstream of the particulate filter 5 to be dispensed with altogether.

- 46 -

[00079] The NO₂-producing catalytic converter 13 may, as shown in Figure 3, be designed as a separate component. Alternatively, it may be integrated into the relevant component at the outlet end of the NO_x storage catalytic converter 6 or at the inlet end of the SCR catalytic converter 7 or may be dispensed with altogether. In an embodiment which is not illustrated, it is possible for a further oxidation catalytic converter to be connected upstream of the NO_x storage catalytic converter 6, which can further reduce the HC and CO emissions in particular during a cold start.

[00080] Figure 4 shows a further variant, in which the exhaust gas aftertreatment installation has a combined SCR and nitrogen oxide storage catalytic converter 15, which combines the functions of the NO_x storage catalytic converter 6 and the SCR catalytic converter 7 from the examples shown in Figs. 1 to 3. An oxidation catalytic converter 4 is connected directly upstream of both this integrated catalytic converter 15 and the downstream particulate filter 5. The other components in accordance with the examples shown in Figure 1 to 3 have been arranged suitably for the positioning of these exhaust gas purification components 4, 5, 15, as shown.

[00081] The integrated catalytic converter 15 can be realized, for example, by using an SCR catalytic converter which is produced as an

- 47 -

unsupported extrudate, with the catalytic material of the SCR catalytic converter serving as a support for a further catalytic coating, specifically a nitrogen oxide storage catalyst coating. Alternatively, it is also possible, in the case of an SCR catalytic converter which is not produced as an unsupported extrudate, to apply a nitrogen oxide storage catalyst coating in addition to the SCR coating. In any case, it is advantageous that this measure considerably reduces the space required. Moreover, both functional components reach the required operating temperature very soon after a cold start, which means that scarcely any additional heating measures, which would increase the fuel consumption, are required.

[00082] During standard lean-burn operation of the internal combustion engine 1, CO and HC are oxidized at the oxidation catalytic converter 4 close to the engine, to form CO₂ and H₂O. A significant proportion of the nitrogen oxide contained in the exhaust gas is temporarily stored in the integrated nitrogen oxide storage and SCR catalytic converter 15, while the remainder is reduced by ammonia which is temporarily stored therein.

[00083] In the example shown in Figure 4, the times of NSC regenerations are determined with the aid of the NO_x sensor 9 downstream of the integrated, combined catalytic converter 15, or

- 48 -

alternatively by one of the other methods described above. In this case, the models stored in the control unit 2 comprise a model relating to the nitrogen oxide storage properties, the ammonia storage properties and the ammonia generation properties of the combined catalytic converter 15.

[00084] In the example shown in Figure 3 ~~4~~, the temperature of the combined catalytic converter 15, which can be recorded by the downstream temperature sensor 8, is an important criterion for the operating parameters of an impending NSC regeneration and targeted generation of ammonia. In addition, it is also possible, for example, for the current ammonia loading, determined on the basis of a model, of the combined catalytic converter 15 to be used as a further criterion. Maximum formation of NH_3 may be aimed for, for example, if the temperature of the combined catalytic converter 15 is within a predetermined range of, for example, between 230°C and 370°C and the current NH_3 loading of the combined catalytic converter 15 is low, and also any further conditions are satisfied.

[00085] The device 11 for supplying reducing agent downstream of the engine which is arranged upstream of the oxidation catalytic converter 4 close to the engine can be used to heat the integrated, combined catalytic converter 15 for the purpose of desulfating of the nitrogen

- 49 -

oxide storage catalyst coating, with the support of additional engine heating measures, as explained above. The quantity of reducing agent supplied is controlled, inter alia, as a function of the following parameters: the desired temperature of the combined catalytic converter 15, the actual temperature of the combined catalytic converter 15 and the mass flow of exhaust gas.

[00086] The oxidation catalytic converter 4 connected upstream of the particulate filter 5 and the device 11 for supplying reducing agent downstream of the engine which is connected upstream of this oxidation catalytic converter 4 can be used to heat the particulate filter. In this arrangement, the combined nitrogen oxide storage and SCR catalytic converter 15 once again remains free of the thermal loading caused by the particulate filter heating. The quantity of reducing agent supplied is controlled, inter alia, as a function of the following parameters: the desired temperature of the particulate filter 5, the actual exhaust gas temperature upstream of the oxidation catalytic converter 4, the actual exhaust gas temperature downstream of the particulate filter 5 and the mass flow of exhaust gas.

[00087] It is advantageous in the exemplary embodiment shown in Figure 4 that the combined nitrogen oxide storage and SCR catalytic converter 15 is protected from high temperatures during the thermal

- 50 -

regeneration of the particulate filter 5 and there is no need for an additional oxidation catalytic converter as a final exhaust gas purification system component for oxidizing the undesirable exhaust gas components when secondary air is blown in. The particulate filter 5 may be catalytically coated, in particular with a catalytic coating similar to that of the upstream oxidation catalytic converter 4. In this case the upstream oxidation catalytic converter 4 can be designed to be smaller or with a lower precious metal content, which leads to corresponding space and/or cost benefits. It is optionally also possible for the oxidation catalytic converter 4 connected upstream of the particulate filter 5 to be dispensed with altogether.

[00088] The SCR catalyst coating and the nitrogen oxide storage catalyst coating can be applied to a support in suitably mixed form in the combined catalytic converter 15. Alternatively, it is possible for the two coatings to be applied alternately in the direction of flow of the exhaust gas, so that the exhaust gas firstly flows through a region comprising nitrogen oxide storage catalyst coating, then a region comprising SCR catalyst coating, then another region comprising nitrogen oxide storage catalyst coating, etc. This embodiment can also be realized by alternately arranging disks of a nitrogen oxide storage catalytic converter and disks of an SCR catalytic converter in series in a

- 51 -

housing. The repeatedly alternating arrangement in the direction of flow of the exhaust gas has the advantage over a mixed combination of the two catalyst materials of resulting in a wider temperature window in which the system operates efficiently. For example, temperature peaks in the front region of the system have a less pronounced effect, for example during the formation of ammonia, if nitrogen oxide storage catalytic converter and SCR catalytic converter are in a repeatedly alternating arrangement than if an arrangement comprising a nitrogen oxide storage catalytic converter and a separate, downstream SCR catalytic converter is used.

[00089] Figure 5 shows an exemplary embodiment in which the internal combustion engine 1 has a two-flow section of the exhaust train 3, with a suitably assigned exhaust gas aftertreatment installation. The latter comprises an NO_x storage catalytic converter 6, an NO₂-producing catalytic converter 13 and an SCR catalytic converter 7, as well as associated sensor means 8, 9, 10 and device 11 for supplying reducing agent downstream of the engine, at suitable positions in accordance with the examples shown in Figs. 1 to 4, arranged identically and symmetrically in each of the two parallel exhaust train sections. The two parallel exhaust trains are combined downstream of the two SCR catalytic converters 7 to form a subsequent single exhaust train section,

- 52 -

in which the particulate filter 5, as well as an oxidation catalytic converter 4 connected directly upstream of it and suitable sensor means 8, 9, 14, device 11 for supplying reducing agent downstream of the engine and device 12 for supplying secondary air, are arranged, as shown.

[00090] A two-flow arrangement of this type may be appropriate, for example, for engines whereof the cylinders are in a V arrangement. It is a required condition that if exhaust gas turbo-charging is being used, a separate turbocharger be employed for each cylinder bank, since otherwise the two flows have to be combined upstream of the turbine of the turbocharger. The operating strategy for this exhaust gas aftertreatment system is such that only minor modifications are required compared to the operating mode of a single-flow system. This is important, since otherwise expensive new development of additional functions would be required in the control unit 2 of the internal combustion engine 1. Moreover, this approach allows the number of sensors used, and therefore the increased costs for the system as a whole, to be limited. The basic concept is for the two parallel trains to be considered as a single train, so that in principle the same operations take place in both trains. This is only possible if the two trains do not fundamentally differ with regard to untreated engine emissions,

- 53 -

catalytic converter types and catalytic converter volumes, etc. More complex approaches, such as for example trains which are operated completely independently of one another and also, for example, time-offset phases of rich exhaust gas, so that lean exhaust gas is always present downstream of the point where the two trains are combined, are alternative options.

[00091] The operating mode of this two-flow system substantially corresponds to that of the single-flow system illustrated in Figure 3, in which the exhaust gas purification components 4 to 7 and 13 are arranged in the same order, and consequently in this respect, reference can be made to the explanations given above in the example shown in Figure 3. The corresponding processes in each case take place independently and in parallel in the two parallel exhaust train sections. A simple functional structure can be maintained for the control unit 2 by virtue of the fact that in the stored model the fundamentally identical catalytic converters 6 and 7, which are in each case arranged in parallel, of the two parallel exhaust train sections are in each case combined to form a single catalytic converter of double the volume. In one advantageous realization, if differences are detected between the two train sections with regard to the demand for NSC regeneration, it is possible to provide for an NSC regeneration to be initiated even if NO_x

- 54 -

emissions which exceed the predetermined threshold value are detected at only one of the two NO_x storage catalytic converters 6. Alternatively, the signals from the NO_x sensors 9 downstream of the NO_x storage catalytic converters 6 can be used in averaged or other weighted form as a representative nitrogen oxide concentration downstream of the NO_x storage catalytic converter for the NSC model in the control unit 2.

[00092] When the aim is for high levels of ammonia to be formed, one of the two lambda sensors 10 downstream of the two parallel NO_x storage catalytic converters 6 measuring a value below the associated threshold value λ_1 can be used as a criterion for terminating NSC regenerations. If the aim is for no ammonia to be formed, the NSC regeneration is, for example, terminated as soon as the air ratio downstream of one of the two parallel NO_x storage catalytic converters 6 drops below the threshold value λ_2 .

[00093] An advantage of the exemplary embodiment shown in Figure 5 is that, despite the geometry of the exhaust system differing significantly, the operating strategy remains similar to that used for the single-flow system shown in Figure 3, and the properties and effects explained above in connection with this single-flow system are achieved in the same way, without any significant additional functions having to be provided for the control unit 2.

- 55 -

[00094] As an alternative to the example shown, it is also possible for the two parallel exhaust train sections to be combined to form a subsequent single-flow train section immediately downstream of the two parallel NO_x storage catalytic converters 6; in this case, there is then only one SCR catalytic converter 7 with upstream optional NO₂-producing catalytic converter 13, located in this single-flow train section. In further alternative embodiments, it is possible to use integrated nitrogen oxide storage and SCR catalytic converters in each of the plurality of train sections, in accordance with the example shown in Figure 4, and/or to use a different order of the exhaust gas purification components, in particular in accordance with Figure 1, 2 and 4.

[00095] Whereas the exemplary embodiments shown refer to an internal combustion engine of a motor vehicle, it will be understood that the exhaust gas aftertreatment installation according to the invention and the exhaust gas aftertreatment method according to the invention, as illustrated and explained above with reference to the examples shown, can also be used for other, for example stationary combustion devices which generate an exhaust gas which needs to be purified.